

FlashRunner Series Comparison Table

DC01388



Features	FlashRunner I Series					FlashRunner II Series	FlashRunner III Series
	FR01ENG	FR01USB	FR01LAN	FR01PRO	FR01M01		
Programming Support	Universal	Universal	Universal	Universal	Universal	One Manuf.	One Device
Interface	RS-232	USB/RS-232	LAN/RS-232	LAN/RS-232	LAN/RS-232	LAN/RS-232	RS-232
ISP Sites	1	1	1	1	8 (Multiplexed)	1	1
ISP Connector Type	Header	D-Sub	D-Sub	D-Sub	Header	D-Sub	D-Sub
Power Supply	9-24V DC	9-24V DC	9-24V DC	110/220V AC	9-24V DC	9-24V DC	7.5V DC
SD Card (up to 2GB)	Yes (FAT16)	Yes (FAT16)	Yes (FAT16)	Yes (FAT16)	Yes (FAT16)	Yes (FAT16)	Yes
Logs/Reports	Yes	Yes	Yes	Yes	Yes	Yes	No
On-Board Dynamic Memory	512 Bytes	512 Bytes	512 Bytes	512 Bytes	512 Bytes	512 Bytes	-
Scripts (Host Mode)	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	Unlimited	1
Scripts (Standalone Mode)	32	32	32	32	32	32	1
Dimensions (mm)	130 x 74 x 27	130 x 74 x 27	130 x 74 x 43	360 x 210 x 45	130 x 74 x 43	130 x 74 x 43	90 x 53 x 33
Real-Time Clock/Calendar	Yes	Yes	Yes	Yes	Yes	Yes	No
Optoisolation	Yes	Yes	Yes	Yes	Yes	Yes	No